

(19) World Intellectual Property  
Organization  
International Bureau



549786


(43) International Publication Date  
30 September 2004 (30.09.2004)

PCT

(10) International Publication Number  
**WO 2004/083103 A1**

- (51) International Patent Classification<sup>7</sup>: **B67D 5/02** (74) Agent: CURRIER, T., Andrew; Torys LLP, Suite 3000, PO Box 270, 79 Wellington, Toronto, Ontario M5K 1N2 (CA).
- (21) International Application Number: PCT/CA2003/000364 (81) Designated States (*national*): CA, US.
- (22) International Filing Date: 19 March 2003 (19.03.2003) Published: — with international search report
- (25) Filing Language: English
- (26) Publication Language: English For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.
- (71) Applicants and  
(72) Inventors: ALEX, Peter [CA/CA]; R.R. #2, Cloverville, Antigonish Co., Nova Scotia B2G 2K9 (CA). LAURELJS, Johnny [CA/CA]; P.O. Box 760, 109 Poplar Street, Stellarton, Nova Scotia B0K 1S0 (CA). CHISHOLM, Ronald, R. [CA/CA]; 189 Lyman Street, Truro, Nova Scotia B2N 4S5 (CA).

(54) Title: FLUID TRANSFER APPARATUS



(57) Abstract: The present invention provides a fluid transfer system (10) comprising: a fluid container (12) configured to receive a liquid, an apparatus (14) for pressurizing the liquid in the container, comprising a deformable envelope (26) defining a space (28) for receiving a gas, a deformation of the envelope effecting a contraction of the space to a contracted condition, such that, when the space includes the gas, the deformation of the envelope results in the contraction of the space to effect a transfer of at least a portion of the gas to the container to thereby effect pressurization of the liquid in the container, a dispensing nozzle (16) including: a fluid passage having a nozzle inlet, a nozzle outlet, and an orifice for effecting fluid communication between the nozzle inlet and the nozzle outlet, the orifice being defined by a valve seat, the nozzle inlet fluidly communicating with the container for effecting a discharge of the liquid from the container, a sealing member biased into sealing engagement with the valve seat for sealing fluid communication between the nozzle inlet and the nozzle outlet, and a manually operated actuator for effecting displacement of the sealing member from the valve seat to effect fluid communication between the nozzle inlet and the nozzle outlet.

WO 2004/083103 A1